

Grand Majestic Comfort

Technical data.

BERRY  ALLOC

04/2025

	contains	m ²	t ²	weight
1 pack Grand Majestic Comfort	3 planks	2,19 m ²	23,58 t ²	21,7 kg
1 pallet Grand Majestic Comfort	42 packs	92,01 m ²	990,38 t ²	952,7 kg

product specifications

Dimensions	2410 x 303 mm
Total thickness	12,3mm (10,3 + 2)
Bevels	4
Loc System	Aluloc Prime
Level of use according to European standard EN10874	23 heavy domestic use
	34 heavy commercial use
Residential warranty	lifetime
Commercial warranty	10 years

Warranty conditions on www.berryalloc.com.



composition

Surface layer	AC6, High pressure laminate, impregnated with melamine and phenol resin
Substrate	Water resistant High Density Fiberboard (+950 kg/m ³)
Backing	Engineered balancing foil
Underlay material	BerryAlloc SilentSystem, attached to the reversed side of the board

test results

Abrasion resistance	EN13329	AC6 (IP≥8500)
Impact resistance	EN13329	small ball : ≥ 15 N - big ball ≥ 1600 mm)
Thickness swelling	ISO 24336	7 % (requirement ≤ 8 %)
Water resistance	ISO 4760	lifetime (according to warranty conditions)
Fire resistance	EN13501-1	Bfl-S1
Formaldehyde emission	EN717-1	E1
Slip resistance	EN13893	DS
Density	EN323	950 kg/m ³
Resistance to staining	EN438.2.26	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN424	no damage (foot type 0)
Effect of a castor chair	EN425	No damage or visible change in appearance at 25.000 rev. with hard wheels (type H)
Thermal resistance with integrated underlay	ISO 8302 (EN12664 / EN12667)	0,13 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com .

high pressure floors.



www.berryalloc.com


Grand Majestic Comfort

Technical data.

BERRY  ALLOC

04/2025

What is a High Pressure Floor made of?



- ❶ AC6 overlay/Class 34
- ❷ Impregnated **decor paper**
- ❸ SPL Laminat
- ❹ Glue paper
- ❺ Water resistant HDF board
- ❻ Counterbalance paper
- ❼ Silent System
- ❽ AluLoc Prime

high pressure floors.