



Bona Clean R60

RESILIENT FLOOR MAINTENANCE

Dual action, cleaning and maintenance of resilient flooring.



Bona Clean R60 is a mild, water-soluble maintenance product for the routine cleaning and care of resilient floors. It has dual action properties, cleaning and leaving a thin, protective film in one simple step. Bona Clean R60 can give a subtle increase in gloss and is compatible with the Bona Resilient System and other resilient floors.

- Cleaning and Maintenance in one
- Leaves a resoluble protective film
- Low foaming



Bona Clean R60

RESILIENT FLOOR MAINTENANCE

Dual action, cleaning and maintenance of resilient flooring.

TECHNICAL DATA

Product type:	Surfactant solution
pH-value:	approx. 9.5 (concentrate)
Dilution:	typically, 50 ml to 10 litres (1:200) (see below for alternatives)
Coverage:	Initial maintenance, 1 litre = 1000 m ²
Application tools:	Bona Microfiber Cleaning Pad
Shelf life:	3 years from date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size	3 x 5 litres

DIRECTIONS FOR USE

Routine Cleaning

1. Remove loose dirt from the floor with dry methods (vacuuming, sweeping).
2. Dilute Bona Clean R60, 50 ml to 10 litres cold water, and wipe the floor with the solution. Let dry. Where heavy contamination is present, the cleaner concentration can be increased to 250 ml per 10 litres of water.

Initial Maintenance

Bona Clean R60 is also suitable for the initial maintenance of resilient floors following final cleaning after installation/renovation.

1. Remove loose dirt from the floor with dry methods (vacuuming, sweeping).
2. Add 1 litre of Bona Clean R60 to 10 litres of cold water and wipe the floor with the solution. Let dry.
3. Use a white polishing pad and a single disc machine to polish the floor. For auto scrubbers, Bona Clean R60 can be diluted with 25 ml into 10 liters of cold water (1:400 ratio).

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.