



Bona Wax Oil

WOOD FLOOR MAINTENANCE

For periodic maintenance of oiled and hard wax oiled surfaces



Bona Wax Oil is a durable wax oil for periodic maintenance of oiled and hardwax oiled surfaces. Restores dry oiled wood floors while adding a protective layer of wax which creates an increased resistance to water and spills. Consists of a concentrate of natural oils and waxes, containing less than 2% solvents.

- Restores and protects
- Low solvent content and low odour

TECHNICAL DATA

Product base:	Emulsified vegetable oils and waxes
Solid content:	Ca. 70 %
VOC:	< 2 %
Dilution:	Do not dilute
Drying time:	Minimum 12 hours* *under normal indoor conditions, 20°C/60% R.H. Ensure proper ventilation
Application tools:	Bona WoolPad or stainless-steel trowel
Coverage:	~50-80 m ² /liter depending on the condition of the floor and wood type
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	3 years, from date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	6 x 1 liter, plastic can (60 boxes per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.



Bona Wax Oil

WOOD FLOOR MAINTENANCE

For periodic maintenance of oiled and hard wax oiled surfaces

PREPARATIONS

If necessary, the previously oiled surface must be thoroughly cleaned with Bona Oil Soap or Bona Deep Clean Solution, and allowed to dry, prior to application of wax oil. Allow product to reach room temperature and shake the container thoroughly before use. **Minimum temperature for use is 16°C.**

APPLICATION

1. Apply Bona Wax Oil thinly using a Bona WoolPad or a stainless-steel trowel. **Note:** The liquid wax oil may contain larger particles of wax. This is normal. The wax is softened and smeared out during the buffing process.
2. Without delay, remove surplus material with cotton cloths and let the surface dry for minimum 12 hours. Expect longer drying time on dense, exotic wood and if the temperature is low.

**WARNING: BONA WAX OIL CONTAINS DRYING OILS.
RISK OF SELF-IGNITION. USED CLOTHS, RAGS, WOOL
PADS AND SIMILAR MATERIAL SHOULD BE PLACED IN
WATER OR SEALED METAL CONTAINERS.**

MAINTENANCE

Clean the floor regularly using a dry mop and/or a vacuum cleaner. When needed, wipe off with a damp mop with Bona Oil Soap added to the cleaning water. Always clean using as dry a method as possible. Apply Bona Wax Oil frequently to ensure that the pores of the surface remain saturated and unable to pick up dirt and moisture. The frequency of this operation is determined by the level of wear and may range from every 3rd year in a domestic environment to a few times a year in a commercial setting. Detailed maintenance instructions are available at www.bona.com